

# ROTOR RAKE

- PULVERIZE SOIL
  - REMOVE DEBRIS
  - FINISH GRADING
- TILLING
  - WINDROWING
  - SWALE MAKING
- SPREADING FILL OR SOIL
  - TRAIL GROOMING & MAINTENANCE
  - DETHATCHING
- SEEDING
  - SCARIFIES FROZEN SURFACES
  - EQUESTRIAN MAINTENANCE



**SPECIFICATIONS** - Part # RR72

Working Width 72"	Width 80"	Height 30"	Weight 1000 lb	Drum Torque @ 2500 PSI 550 ft-lbs	GPM Range 8-30	3000 PSI Max	Drum Speed 0-600 RPM
----------------------	--------------	---------------	-------------------	--------------------------------------	-------------------	-----------------	-------------------------

RotoRake's bi-directional 2-speed rotor allows for operation in both directions. Features a 25 degree angle and 28 degree tilt for ease in swaling and ditching. Oscillating gauge wheels lock in level position for the 3 point hitch use. Dual motor design delivers 40% more power and elimination of outside bearings and chains. RotoRake also features a floating rotor design, increased durability with carbide teeth, ditch cutters and side shields. RotoRake can be used on a 3 point hitch or skid steer hitch systems. Optional PTO pump and tank kits available.

**REIST Industries Elmira, Ontario, Canada 1-877-467-3478**  
**Reist Industries USA 844 E. Greenwood Street, Abbeville SC 29620 1-888-369-1444**  
[www.reistindustries.com](http://www.reistindustries.com)

FOR MORE INFORMATION PLEASE CONTACT

"Under our policy of continuous improvement, we reserve the right to change specifications and designs without prior notice. The illustrations do not necessarily show the standard version of product offered by REIST Industries."